



Product feature

- Air temp. servo-controlled by computer
- Removable humidity reservoir, easy to clean
- Separate setting temp. air temp., skin temp. display windows
- Various and self-check alarms
- With the transfusion shelf and tray
- RS-232 connector
- Free-step mattress tilting adjustment
- Phototherapy (option)
- Skin temp. servo-controlled by computer (option)



Phototherapy unit(option)
BBP-1000B/2000B



Monitor tray



The humidity reservoir is removable



Phototherapy unit(option)
BBP-3000B

Specifications Infant Incubator

Model	BIN-3000A
Electrical requirement	~ 220V 50Hz or ~ 230V 60Hz
Power consumption	≤ 450VA
Air mode temp. range	25.0°C ~ 37.0°C
Skin mode temp. range	25.0°C ~ 37.0°C
Air over temp. range	< 38.0°C
Air mode high temp. range	37.1°C ~ 39.0°C
Skin mode high temp. range	37.1°C ~ 38.0°C
High temp. mode alarm	< 40.0°C
Air mode alarm	± 3.0°C
Skin mode alarm	± 1.0°C
Skin sensor accuracy	≤ ± 0.3°C
Air control accuracy	≤ 0.5°C
Mattress temp. uniformity	≤ 0.8°C
Noise	≤ 55dB(A)

Exclusive Distributor



PT. PERMANA PUTRA MANDIRI
 MEDICAL EQUIPMENTS SUPPLIES AND SERVICES
 Jl. Taman Mini Indonesia Indah (TMII)
 Pintu II Atas No. 43 Cipayung, Jakarta Timur, Indonesia
 Telp. : +62-21 841 5976, Fax : +62-21 840 7865
 Email : info@ptppm.id, Website : www.ptppm.id